 WARM

## Pink® Batts® Masonry Wall Insulation

### Description

Pink®Batts® insulation designed to fit between strapping members fixed to masonry walls.


### Properties

Thickness/R-Value	19mm	R0.5m²K/W
	25mm	R0.7m²K/W
	● 40mm	R1.0m²K/W
	50mm	R1.2m²K/W
Packaging	19mm	1 per bale
	25mm	1 per bale
	40mm	30 pcs per bale
	50mm	24 pcs per bale
Piece Size:	19 and 25mm	15m x 1.22m
	Other thicknesses	1220 x 580mm

### Installation

Pink®Batts® Masonry Wall Insulation is installed between vertical strapping members against solid (usually masonry) walls.

The product can be used in specific design installations to assist in meeting the R-values called up in NZS 4218:2004 as an acceptable solution to meeting New Zealand Building Code clause H1 Energy Efficiency. Pieces must be installed with a friction fit, ensuring no gaps or folds in the finished job. In some cases, particularly when using 19 or 25mm insulation it may be desirable to staple the top of the insulation onto the surrounding batten, to hold the insulation temporarily until the wall linings are in place. In this case staple product onto the battens on each side, with the first staple 100mm down from the top of the wall and then two further staples at about 150mm centres below the first. We recommend that a building paper be placed between the insulation and the concrete. This is not intended to replace the DPC which must still be fixed between strapping and masonry.



**BRANZ Appraised**  
Appraisal No. 238 [2008]

This brochure supersedes all previous brochures. Tasman Insulation New Zealand retain the right to change products and specifications without prior notification. If a specification is critical to the end use, please consult Tasman Insulation New Zealand. Do not use this product in an application other than that detailed in this data sheet, without obtaining written advice from Tasman Insulation New Zealand. All product dimensions and performance claims are subject to any variation caused by

normal manufacturing process and tolerances. This information is provided without prejudice to Tasman Insulation New Zealand standard terms and conditions of sale. Tasman Insulation is a Fletcher Building Company.

**AUCKLAND:** P.O. Box 12069, Penrose. Ph: (09) 579-2139. Fax: (09) 579-8806.  
**WELLINGTON:** P.O. Box 51366, Tawa. Ph: (04) 232-1576. Fax: (04) 232-1564.  
**CHRISTCHURCH:** P.O. Box 16000, Hornby. Ph: (03) 349-9059. Fax: (03) 349-4261.